MULE[™] 4010 4x4 FE





MSRP **\$12,199**



BRIGHT WHITE



POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 2.99 x 2.68 in

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output

(max)

23 amp

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in Wheel Travel

Rear Suspension / Wheel Travel DeDion Axle/2.8 in

Front Tires 23x11.00-10

Rear Tires 23x11.00-10

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Front Brakes Drum
Rear Brakes Drum

Park Brake Type Independent, Mechanical Drum

Ground Clearance 6.9 in

Turning Radius 11.2 ft

......

Cargo Bed Dimensions (LxWxH)

Cargo Bed Load

Payload Capacity

Fuel Capacity

Capacity

1,312 lb

800 lb

6.3 gal

46.3 x 51.6 x 11.4 in

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

DETAILS

Overall Length 116.7 in
Overall Width 62.0 in

Overall Height 78.1 in

Curb Weight 1,448.7 lb*

Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning

light, horn, 12V DC outlet, fuel gauge, hour meter

Wheel Type Steel

Additional Features Roof, Horn, Universal Key, High Visibility Orange Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24 or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



