

2023
KX™ 65



MSRP
\$3,999



POWER		Front Brakes	Single 180mm disc with single-piston caliper
Engine	2-stroke single, liquid-cooled	Rear Brakes	Single 180mm disc with single-piston caliper
Displacement	64cc	DETAILS	
Bore x Stroke	45.5 x 41.6mm	Frame Type	High-tensile steel semi-double cradle
Compression Ratio	8.4:1	Rake/Trail	27° / 2.4 in
Fuel System	24mm Mikuni carburetor	Overall Length	62.6 in
Ignition	CDI with Digital Advance	Overall Width	29.9 in
Transmission	6-speed, return shift, with wet multi-disc manual clutch	Overall Height	37.6 in
Final Drive	Chain	Ground Clearance	12.0 in
PERFORMANCE		Seat Height	29.9 in
Front Suspension / Wheel Travel	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in	Curb Weight	132.2 lb*
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in	Fuel Capacity	1.0 gal
Front Tire	60/100-14	Wheelbase	44.1 in
Rear Tire	80/100-12	Color Choices	Lime Green
		Warranty	Not Available
		Kawasaki Protection Plus™ (optional)	Not Available

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.