2023 TERYX4™

Let the Good Times Rol



MSRP \$16,199



METALLIC SIERRA BLUE/METALLIC ONYX BLACK



17.9 x 47.6 x 8.7 in

249 lb

1,109 lb

1,300 lb

stoplight

POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with two 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive

Engine Braking Yes

Selectable 2WD/4WD with locking front differential, shaft

CAPABILITY

Front Suspension / **Wheel Travel**

Double Wishbone; FOX Podium coil-over shocks with piggyback reservoir, adjustable preload and 24-way

compression damping/8.0 in

Rear Suspension / Double Wishbone; FOX Podium coil-over shocks with **Wheel Travel** piggyback reservoir, adjustable preload and 24-way

compression damping/8.3 in

Front Tires Maxxis® 26 x 9-12

Rear Tires Maxxis® 26 x 11-12

Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with two-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc

Ground Clearance 11.2 in **Fuel Capacity** 7.9 gal **Turning Radius** 16.7 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

(2) incandescent headlights, (2) LED taillights, LED

DETAILS

Steel Tube Double-X Reinforcement **Frame**

Overall Length 125.4 in **Overall Width** 60.0 in

Overall Height 77.8 in

Curb Weight 1,605.2 lb*

Wheelbase 85.6 in

Instruments Multi-function digital meter with speedometer, fuel gauge,

> clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Wheel Type Steel

Color Choices Metallic Sierra Blue/Metallic Onyx Black

Kawasaki Strong 3-Year Limited Warranty Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.

