MULE PRO-FXT™ 1000 LE





\$18,799



METALLIC SIERRA BLUE



METALLIC ONYX BLACK



POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

999cc Displacement **Maximum Torque** 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

Fuel System DFI® with 38mm throttle body

Continuously Variable Transmission (CVT) with (L,H,N,R) **Transmission**

Selectable 2WD/4WD, shaft Dual mode rear differential with **Final Drive**

differential lock

Engine Braking

Alternator Output 90 amp

(max)

7.9 gal **Fuel Capacity**

42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-**Cargo Bed** Dimensions (LxWxH)

person)

16.0 ft

Cargo Bed Load Capacity

Turning Radius

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/11.0 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/10.1 in

Front Tires 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper **Park Brake Type** Independent, Mechanical Disc

Ground Clearance 12.6 in (max), 11.6 in (std) **DETAILS**

Overall Length 135.8 in

Overall Width 64.0 in **Overall Height** 80.9 in

Curb Weight 1,913.9 lb* / 1,916.1 lb* CA Model

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps

999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Wheel Type

Additional Features Roof, Additional Front Cup Holders

Color Choices Metallic Onyx Black, Metallic Sierra Blue

Warranty Kawasaki STRONG 3-Year Limited Warranty

Kawasaki Protection 12, 24, 36, or 48 months Plus™ (optional)

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.