2024 NINJA[®] ZX[™]-4RR 40th ANNIVERSARY EDITION ABS







Dual 290mm discs, ABS

Single 220mm disc, ABS

POWER

Engine	4-stroke, In-Line Four, OHC, 16-valve, liquid- cooled
Displacement	399сс
Bore x Stroke	57.0 x 39.1mm
Compression Ratio	12.3:1
Fuel System	DFI® with 34mm throttle valves (4)
Ignition	Digital
Transmission	6-speed, manual, return shift
Final Drive	Chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC) (3-mode), Kawasaki Quick Shifter (KQS) (dual direction), Economical Riding Indicator, Power Modes, Anti- lock Brake System (ABS)

DETAILS **Frame Type** Trellis, high-tensile steel 23.5°/3.8 in Rake/Trail **Overall Length** 78.3 in **Overall Width** 30.1 in **Overall Height** 43.7 in 5.3 in Ground Clearance 31.5 in **Seat Height Curb Weight** 414.5 lb* **Fuel Capacity** 4.0 gal Wheelbase 54.3 in **Special Features** 4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDEOLOGY THE APP **Color Choices** Lime Green/Pearl Crystal White/Blue Warranty 12 Month Limited Warranty Kawasaki 12, 24, 36 or 48 months **Protection Plus™** (optional)

PERFORMANCE

Front Suspension / Wheel Travel	37mm inverted fork with SFF-BP internals and spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal Back-link, BFRC lite gas charged shock w/ piggyback reservoir, adjustable compression, rebound and spring preload/4.9 in
Front Tire	110/70 - 17
Rear Tire	160/60-17



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Front Brakes

Rear Brakes