TERYX4™ S SPECIAL EDITION





\$18,999



ICE GRAY/METALLIC ONYX BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft@ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

Fuel System DFI® with two 36mm Mikuni throttle bodies

TCBI with Electronic Advance Ignition

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **Fuel Capacity Turning Radius**

17.7 ft

Cargo Bed **Dimensions (LxWxH)**

17.9 x 47.6 x 8.7 in

7.9 gal

Cargo Bed Load

Capacity

249 lb

Payload Capacity

1,054 lb

Seating Capacity

Towing Capacity 1,300 lb

Lighting (4) LED headlights, (2) LED taillights, LED stoplight

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / Wheel Travel

Rear Tires

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Maxxis® 27 x 11-14 Electric Power Steering (EPS) / rack-and-pinion **Steering**

Front Brakes Dual hydraulic discs with two-piston calipers

Sealed, oil-bathed, multi-disc **Rear Brakes**

Ground Clearance 11.2 in / 12.2 in

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 125.4 in **Overall Width** 62.6 in 80.5 in **Overall Height**

Curb Weight 1,684.6 lb*

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel

> gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and

low-oil-pressure indicators

Wheel Type Alloy

Color Choices Ice Gray/Metallic Onyx Black

Kawasaki Strong 3-Year Limited Warranty Warranty

Kawasaki Protection 12, 24, or 36 months Plus™ (optional)



