

2024

VULCAN® S

Kawasaki
Let the Good Times Roll®



MSRP NON-ABS
\$7,349

MSRP ABS
\$7,899

-  PEARL SAND KHAKI/EBONY
-  METALLIC FLAT SPARK BLACK



POWER		Front Brakes	Single 300mm disc with twin-piston caliper, (and ABS)
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Brakes	Single 250mm disc with single-piston caliper (and ABS)
Displacement	649cc	DETAILS	
Bore x Stroke	83.0 x 60.0mm	Frame Type	High-tensile steel diamond frame
Compression Ratio	10.8:1	Rake/Trail	31° / 4.7 in
Maximum Torque	46.3 lb-ft @ 6,600 rpm	Overall Length	90.9 in
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves	Overall Width	34.6 in
Ignition	TCBI with Electronic Advance	Overall Height	43.3 in
Transmission	6-speed with positive neutral finder	Ground Clearance	5.1 in
Final Drive	Sealed chain	Seat Height	27.8 in
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)	Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
PERFORMANCE		Fuel Capacity	3.7 gal
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Wheelbase	62.0 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Color Choices	Pearl Sand Khaki/Ebony, Metallic Flat Spark Black
Front Tire	120/70x18	Warranty	12 Month Limited Warranty
Rear Tire	160/60x17	Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.