

Labels

F2860

Kawasaki

ADDITIONAL READER INFORMATION

For more information on this book, contact the publisher at (800) 354-9700 or visit our website at www.mhhe.com.

For more information on this book, contact the publisher at (800) 354-9700 or visit our website at www.mhhe.com.

For more information on this book, contact the publisher at (800) 354-9700 or visit our website at www.mhhe.com.

▲ WARNING
Do not touch hot surfaces

NOTICE
Shifting incorrectly can
damage transmission.
Shift only when :
Engine is at slow idle.
Vehicle is completely
stopped.

▲ WARNING			
Tire replacement, improper tire pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.			
Load condition (including occupants and cargo)	Cold tire pressure	Tire size	
Front Up to 454 kg load (1100 lbs)	82.7 kPa (8.24 bar/12.0 psi)	25x6.0R-12	
Rear Up to 454 kg load (1100 lbs)	82.7 kPa (8.24 bar/12.0 psi)	25x11.00R-12	

A diagram showing a bracket with a cable attached. An arrow points from the left side, where the cable is being cut, to the right side, where the cable has been removed from the bracket.

▲ WARNING
Gasoline is flammable.
Fire can cause severe
injury or death.
Refuel in well
ventilated area.
Shut engine off.
Keep away from
flame or sparks.

▲ WARNING			
The replacement, improper use, pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.			
	Load capacity (including accessories and cargo)	Cut-off pressure	Tire size
Front	Up to 544 kg (1200 lb)	82.7 kPa (0.8 kgf/cm ² , 11.8 psi)	26x10K-12
Rear	Up to 544 kg (1200 lb)	82.7 kPa (0.8 kgf/cm ² , 11.8 psi)	26x12K-12

WARNING

Operating this equipment in the presence of flammable or combustible vapors may expose you to chemicals listed on the product label. Follow the instructions on the label to avoid exposure to these chemicals and to avoid contact with the vapors.

To minimize exposure, avoid breathing vapors and do not get the liquid on your skin. If necessary, remove your clothing, wash your skin, and wash your eyes with plenty of water immediately after contact with the liquid.

For more information go to:
www.PSSB.com or call 1-800-4-A-SEAL

⚠WARNING

Radical distances between the cargo bed and the RCPS may stop an arm while lifting or lowering the cargo bed. This may result in injury.

To avoid possible injury, always use the lift handle provided and do not place hands on the RCPS in the area of the cargo bed while lifting or lowering the cargo bed.

⚠ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle. Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity 272 kg (600 lbs)

Follow the "Loading Information" and "Cargo Bed" sections in the owner's manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.



WARNING

Improperly loading a trailer can cause an accident and injury. Use extra care when loading a trailer. Decrease following distance and use extreme caution when operating on hills. Follow towing rules posted in the Owner's Manual.

*Max. trailer tongue weight: 600 kg (1320 lbs)

*Max. trailer weight: 600 kg (1320 lbs) (trailer plus cargo weight)



WEDCO Inc.

IMPORTANT DRIVE BELT INFORMATION

Proper, clean, and tight belts are essential for maximum car and belt longevity and safety.

Inspection of the transmission drive belt is required at least every 30,000 miles or 24,000 miles (24,000), whichever comes first.

The lowest possible tension is required for the belt to operate properly. If excessive belt tension is required to start engine, if excessive belt slippage occurs, or if the belt is cracked or damaged, replacement is required. Refer to your Owner's Manual.

▲ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle. Loss of control of the vehicle can result in serious injury or death.

Cargo load capacity: 317 kg (700 lbs)

Follow the "Loading Information" and "Cargo load" sections in the owner's manual.

Driving with a passenger in the cargo bed can result in serious injury or death.

Never carry passengers in the cargo bed.

[illegible]

2021 MULE PRO-MX™ PARTS LIST

Labels

ITEM NAME	PART NUMBER	QUANTITY
LABEL,TIRE (Ref # 56030)	56030-Y015	1
LABEL,OIL GAUGE (Ref # 56030A)	56030-Y018	1
LABEL-WARNING,INFO (Ref # 56071)	56071-Y057	1
LABEL-WARNING,SHIFTING NOTICE (Ref # 56071A)	56071-Y058	1
LABEL-WARNING,FUEL (Ref # 56071B)	56071-Y059	1
LABEL-WARNING,AIR CLEANER INFO (Ref # 56071C)	56071-Y060	1
LABEL-WARNING,ROPS (Ref # 56071D)	56071-Y061	1
LABEL-WARNING (Ref # 56071E)	56071-Y062	1
LABEL-WARNING,MAX. CAPACITY (Ref # 56071G)	56071-Y064	1
LABEL-WARNING,GENERAL (Ref # 56071H)	56071-Y065	1
LABEL-WARNING,CARGO BED (Ref # 56071I)	56071-Y066	1
LABEL-WARNING,TIRE (Ref # 56071J)	56071-Y067	1
LABEL-WARNING,HANG TAG (Ref # 56071K)	56071-Y068	1
PATTERN,KAWASAKI (Ref # 56075)	56075-Y001	1