

Labels

F2860

Kawasaki

[illegible]

▲ WARNING
Do not touch hot surfaces

NOTICE
Shifting incorrectly can
damage transmission.
Shift only when :
Engine is at slow idle.
Vehicle is completely
stopped.

▲ WARNING			
Tire replacement, improper tire pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.			
	Load condition (including occupants and cargo)	Cold tire pressure	Tire size
Front	Up to 450 lbs (204 kg) (1100 lbs)	32.7 psi (0.84 kg/cm ²)	25x8-09R-12
Rear	Up to 450 lbs (204 kg) (1100 lbs)	32.7 psi (0.84 kg/cm ²)	35x11-00R-12

A diagram showing a hand using a tool to remove the old sealant from the joint. An arrow points to the right, indicating the direction of removal.

▲WARNING
Gasoline is flammable.
Fire can cause severe
injury or death.

Refuel in well
ventilated area.
Shut engine off.
Keep away from
flame or sparks.

⚠ WARNING			
The replacement, improper use or misuse or overloading can cause loss of control. Loss of control can result in serious injury or death.			
	Load capacity (including occupants and cargo)	Color designation	Tire size
Front	Up to 544 kg load (1200 lbs)	82/70R16 (0.6 m³ capacity, 11.0 psi)	255/40R12
Rear	Up to 544 kg load (1200 lbs)	82/70R16 (0.6 m³ capacity, 11.0 psi)	255/40R12

⚠WARNING

Radical differences between the cargo bed and the RCPS may result in an unstable fit or tipping, the cargo bed. This may result in injury.

To avoid possible injury, always use the fit handle provided and do not place hands on the RCPS in the area of the cargo bed when fitting or detaching the cargo bed.

WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle. Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity: 272 kg (600 lbs).

Follow the "Loading Information" and "Cargo Bed" sections in the owner's manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.

WARNING
 Improperly loading a trailer can cause an accident and injury. Use extra care when loading a trailer. Exceeding a low-range gear only, slow to maintain braking distance, and use extreme caution when operating on hills.
 Follow towing tips provided in the Owner's Manual.
 •Max. trailer weight: 680 kg (1500 lbs)
 •Max. trailer weight: 680 kg (1500 lbs) / trailer plus cargo weight

IMPORTANT DRIVE BELT INFORMATION

Wipe, clean, or lubricate to maintain the function of the belt and pulleys.

Inspection of the transmission drive belt is required if you drive 100,000 or 200,000 miles. Check belts with the engine on.

Never bypass bypass a necessary belt while it is rotated in the belt range. It causes belt damage. Do not use the vehicle with damaged components on engine. Refer to your Owner's Manual.

▲ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle.
 Loss of control of the vehicle can result in severe injury or death.
 Cargo bed capacity: 357 kg (790 lb)
 Follow the "Loading Information" and "Cargo Bed" sections in the owner's manual.
 Driving with a passenger in the cargo bed can result in severe injury or death.
 Never carry passengers in the cargo bed.

⚠ WARNING

Improper Use of Off-Highway Vehicles Can Cause Serious Injury or Death

In Proper Use:

- Read and understand all controls and instructions.
- Use only for the purposes intended.
- Do not drink or use drugs if you will be operating the vehicle.
- Do not operate the vehicle if you are tired or have been drinking.
- Do not drink or use drugs while driving the vehicle.

Proper Use Includes:

- Wearing your seat belt while driving.
- Wearing your seat belt while riding.
- Wearing your seat belt while driving.
- Wearing your seat belt while riding.
- Wearing your seat belt while driving.
- Wearing your seat belt while riding.



Do Not:

- 1. Operate the vehicle while drinking or using drugs.
- 2. Operate the vehicle while driving on a public road.
- 3. Operate the vehicle while driving on a public road.
- 4. Operate the vehicle while driving on a public road.
- 5. Operate the vehicle while driving on a public road.
- 6. Operate the vehicle while driving on a public road.

Do Not:

- 1. Operate the vehicle while drinking or using drugs.
- 2. Operate the vehicle while driving on a public road.
- 3. Operate the vehicle while driving on a public road.
- 4. Operate the vehicle while driving on a public road.
- 5. Operate the vehicle while driving on a public road.
- 6. Operate the vehicle while driving on a public road.



2024 Mule PRO-MX EPS LE PARTS LIST

Labels

ITEM NAME	PART NUMBER	QUANTITY
LABEL,OIL GAUGE (Ref # 56030A)	56030-Y018	1
LABEL-WARNING,INFO (Ref # 56071)	56071-Y057	1
LABEL-WARNING,SHIFTING NOTICE (Ref # 56071A)	56071-Y058	1
LABEL-WARNING,FUEL (Ref # 56071B)	56071-Y059	1
LABEL-WARNING,AIR CLEANER INFO (Ref # 56071C)	56071-Y060	1
LABEL-WARNING,ROPS (Ref # 56071D)	56071-Y061	1
LABEL-WARNING (Ref # 56071E)	56071-Y062	1
LABEL-WARNING,MAX. CAPACITY (Ref # 56071G)	56071-Y064	1
LABEL-WARNING,GENERAL (Ref # 56071H)	56071-Y065	1
PATTERN,KAWASAKI (Ref # 56075)	56075-Y001	1