

Labels

F2860

Kawasaki

[illegible]

▲ WARNING
Do not touch hot surfaces

NOTICE
Shifting incorrectly can
damage transmission.
Shift only when :
Engine is at slow idle.
Vehicle is completely
stopped.

⚠ WARNING			
Tire replacement, improper tire pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.			
	Load position (including occupants and cargo)	Cold tire pressure	Tire size
Front	Up to 450 lbs (203 kg) (1100 lbs)	32.7 psi (0.84 kg/cm ² , 12.0 psi)	25x8.00R-12
Rear	Up to 450 lbs (203 kg) (1100 lbs)	32.7 psi (0.84 kg/cm ² , 12.0 psi)	25x10.00R-12

A diagram showing a bracket being removed from a cable. An arrow points from the bracket on the cable to the bracket alone, indicating the removal of the old cable.

▲ WARNING
Gasoline is flammable.
Firt can cause severe
injury or death.
Refuel in well
ventilated area.
Shut engine off.
Keep away from
flame or sparks.

⚠ WARNING			
This equipment, together with cranes or hoisting gear, can cause loss of control. Loss of control can result in serious injury or death.			
Load condition (including components and dunnage)	Crane capacities	Tie-ups	
Front	Up to 54 kN tie (120 k lb)	82.7 kN (18.6 kN) (12.0 kN)	25 kN (5.6 kN)
Rear	Up to 54 kN tie (120 k lb)	82.7 kN (18.6 kN) (12.0 kN)	25 kN (5.6 kN)

⚠WARNING

Radical differences between the cargo bed and the HCPS may trip or overturn lifting or lowering the cargo bed. This may result in injury.

To avoid possible injury, always use the lift handle provided and do not place hands on the HCPS in the area of the cargo bed when lifting or lowering the cargo bed.

⚠ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle. Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity: 272 kg (600 lbs).

Follow the "Loading Information" and "Cargo Bed" sections in the owner's manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.



WARNING

Improperly loading a trailer can cause an accident and injury. Use good technique when loading a trailer. Observe all loadings per axle only, allow for increased braking distance, and use extreme caution when operating on hills. Follow towing/brake procedures in the Owner's Manual.

- After trailer tongue weight: 88 lb (40 kg)
- Max. total weight: 500 kg (1100 lbs)
- Max. total weight: 500 kg (1100 lbs) (trailer plus cargo weight)

[illegible]

▲ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle.
 Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity: 317 kg (700 lbs)
 Follow the loading instructions and "Cargo load capacity" section in the owners manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.



[illegible]

2025 Mule PRO-MX EPS PARTS LIST

Labels

ITEM NAME	PART NUMBER	QUANTITY
LABEL,OIL GAUGE (Ref # 56030A)	56030-Y018	1
LABEL-WARNING,INFO (Ref # 56071)	56071-Y057	1
LABEL-WARNING,SHIFTING NOTICE (Ref # 56071A)	56071-Y058	1
LABEL-WARNING,FUEL (Ref # 56071B)	56071-Y059	1
LABEL-WARNING,AIR CLEANER INFO (Ref # 56071C)	56071-Y060	1
LABEL-WARNING,ROPS (Ref # 56071D)	56071-Y061	1
LABEL-WARNING (Ref # 56071E)	56071-Y062	1
LABEL-WARNING,MAX. CAPACITY (Ref # 56071G)	56071-Y064	1
LABEL-WARNING,GENERAL (Ref # 56071H)	56071-Y065	1
PATTERN,KAWASAKI (Ref # 56075)	56075-Y001	1