

Labels

F2860

Kawasaki

HOCHTIEF AG
 Postfach 10 15 50 • 42699 Solingen
 Telefon (0212) 240-1 • Telefax (0212) 240-2424
 Telex 923203 • Teletext 848 240
 Telex 923203 • Teletext 848 240
 Telex 923203 • Teletext 848 240

▲ WARNING
Do not touch hot surfaces

NOTICE
Shifting incorrectly can
damage transmission.
Shift only when :
Engine is at slow idle.
Vehicle is completely
stopped.

⚠ WARNING			
Tire replacement, improper tire pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.			
	Load condition (including occupants and cargo)	Cold tire pressure	Tire size
Front	Up to 450 kg load (1000 lbs)	32.7 psi (0.84 kg/cm ² , 12.0 psi)	25x8.00R-12
Rear	Up to 450 kg load (1000 lbs)	32.7 psi (0.84 kg/cm ² , 12.0 psi)	25x10.00R-12

A diagram showing a cross-section of a joint with a T-shaped sealant. An arrow points from the left side, where the sealant is being cut and removed, to the right side, where the sealant has been fully removed, leaving a gap.

▲ WARNING
Gasoline is flammable.
Fires can cause severe
injury or death.
Refuel in well
ventilated area.
Shut engine off.
Keep away from
flame or sparks.

⚠ WARNING			
The replacement separator for creating a secondary tank can cause loss of control. Loss of control can result in serious injury or death.			
	Load limitation (including contents and cargo)	Gross weight pressure	Tank size
Front	Up to 545 kg (1200 lbs) (500 lbs)	0.27 MPa (3.94 kg/cm ²) (2.8 psi)	2500 (1000) L
Rear	Up to 545 kg (1200 lbs) (500 lbs)	0.24 MPa (3.48 kg/cm ²) (2.6 psi)	2500 (1000) L

⚠WARNING

Radical differences between the cargo bed and the RCPS may result in an unstable fit or binding, the cargo bed. This may result in injury.

To avoid possible injury, always use the fit handle provided and do not place hands on the RCPS in the area of the cargo bed when fitting or removing the cargo bed.

⚠ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle. Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity: 272 kg (600 lbs).

Follow the "Loading Information" and "Cargo Bed" sections in the owner's manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.



WARNING

Improperly towing a trailer can cause an accident and injury. Use extra care when towing a trailer. Observe all towage restrictions, allow for increased braking distances, and use extreme caution when operating on hills. Follow towing/brake procedures in the Owner's Manual.

- After trailer tongue weight: 88 lb (40 kg)
- Max. trailer weight: 500 kg (1100 lbs)
- Max. total weight: 500 kg (1100 lbs) (trailer plus cargo weight)

[illegible]

▲ WARNING

Overloading or failure to properly secure cargo can cause loss of control of the vehicle.
 Loss of control of the vehicle can result in severe injury or death.

Cargo bed capacity: 317 kg (700 lbs)
 Follow the loading instructions and "Cargo load capacity" section in the owners manual.

Driving with a passenger in the cargo bed can result in severe injury or death.

Never carry passengers in the cargo bed.

[illegible]

2026 Mule PRO-MX EPS Camo

PARTS LIST

Labels

ITEM NAME	PART NUMBER	QUANTITY
LABEL,OIL GAUGE (Ref # 56030A)	56030-Y018	1
LABEL-WARNING,INFO (Ref # 56071)	56071-Y057	1
LABEL-WARNING,SHIFTING NOTICE (Ref # 56071A)	56071-Y058	1
LABEL-WARNING,FUEL (Ref # 56071B)	56071-Y059	1
LABEL-WARNING,AIR CLEANER INFO (Ref # 56071C)	56071-Y060	1
LABEL-WARNING,ROPS (Ref # 56071D)	56071-Y061	1
LABEL-WARNING,HOT SURFACE (Ref # 56071E)	56071-Y062	1
LABEL-WARNING,MAX. CAPACITY (Ref # 56071G)	56071-Y064	1
LABEL-WARNING,GENERAL (Ref # 56071H)	56071-Y065	1
PATTERN,KAWASAKI (Ref # 56075)	56075-Y001	1