JET SKI[®] ULTRA[®] 310X









CANDY STEEL FURNACE ORANGE/EBONY



POWER

Engine	Supercharged and intercooled, 4-stroke, DOHC, four valves per cylinder, inline 4-cylinder
Displacement	1,498cc
Bore x Stroke	83.0 x 69.2mm
Compression Ratio	8.2:1
Induction	Eaton Twin Vortices Series Roots-type supercharger with air-to-water intercooler
Maximum Boost	16.8 psi
Cooling System	Inducted water
Fuel System	DFI® with 60mm throttle body
Ignition	TCBI with digital advance
Starting System	Electric
Propulsion System	160mm jet pump, axial-flow, single stage
Impeller	3-blade, oval-edge stainless steel
Thrust	1890 lb

PERFORMANCE

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.8 qt.
Fuel Capacity	20.6 gal.
Load Capacity	496 lb.
Storage Capacity	56 gal.

DETAILS

Overall Length	132.7 in.
Overall Width	47.0 in.
Overall Height	45.3 in.
Curb Weight	1051.8 lb.*
Seating Capacity	3
Color Choices	Candy Steel Furnace Orange/Ebony
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.