

2020

# NINJA H2™R

**Kawasaki**  
Let the Good Times Roll®



MSRP  
**\$55,000**

 MIRROR COATED MATTE SPARK BLACK



| POWER                 |                                                                                                                                                                                                                                                                                                |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                | 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled, supercharged                                                                                                                                                                                                                               |
| Displacement          | 998cc                                                                                                                                                                                                                                                                                          |
| Bore x Stroke         | 76.0 x 55.0mm                                                                                                                                                                                                                                                                                  |
| Compression Ratio     | 8.3:1                                                                                                                                                                                                                                                                                          |
| Fuel System           | DFI® with 50mm throttle bodies (4) with dual injection                                                                                                                                                                                                                                         |
| Ignition              | TCBI with digital advance                                                                                                                                                                                                                                                                      |
| Transmission          | 6-speed, return, dog-ring                                                                                                                                                                                                                                                                      |
| Final Drive           | Sealed chain                                                                                                                                                                                                                                                                                   |
| Electronic Rider Aids | Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper |

|                                |                                                                                                                                                                                                    |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Suspension / Wheel Travel | Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping and adjustability, and hand-turn spring preload adjustability and top-out spring/5.3 in |
| Front Tire                     | 120/60 ZR17 Bridgestone V01F slick                                                                                                                                                                 |
| Rear Tire                      | 190/65 ZR17 Bridgestone V01R slick                                                                                                                                                                 |
| Front Brakes                   | Dual radial-mount, opposed 4-piston M50 calipers, dual semi-floating 330mm discs, KIBS ABS                                                                                                         |
| Rear Brakes                    | Opposed 2-piston calipers, single 250mm disc, KIBS ABS                                                                                                                                             |

| PERFORMANCE                     |                                                                                                                             |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in |

| DETAILS          |                                                           |
|------------------|-----------------------------------------------------------|
| Frame Type       | Trellis, high-tensile steel, with swingarm mounting plate |
| Rake/Trail       | 25.1° / 4.3 in                                            |
| Overall Length   | 81.5 in                                                   |
| Overall Width    | 33.5 in                                                   |
| Overall Height   | 45.7 in                                                   |
| Ground Clearance | 5.1 in                                                    |
| Seat Height      | 32.7 in                                                   |
| Curb Weight      | 476.3 lb*                                                 |
| Fuel Capacity    | 4.5 gal                                                   |
| Wheelbase        | 57.1 in                                                   |
| Special Features | N/A                                                       |
| Color Choices    | Mirror Coated Matte Spark Black                           |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.