2021 **VERSYS® 650 ABS**





^{MSRP} **\$8,399**



METALLIC MOONDUST GRAY/METALLIC SPARK BLACK



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, 4 valves per cylinder parallel twin	
Displacement	649cc	
Bore x Stroke	83.0 x 60.0mm	
Compression Ratio	10.8:1	
Maximum Torque	47.0 lb-ft	
Fuel System	DFI® with 38mm Keihin throttle bodies (2)	
Ignition	TCBI with electronic advance	
Transmission	6-speed with positive neutral finder	
Final Drive	Sealed chain	

Front Tire 120/70 ZR-17 **Rear Tire** 160/60 ZR-17 **Front Brakes** Dual 300mm petal-style discs with 2-piston calipers, ABS **Rear Brakes** Single 250mm petal-style disc with singlepiston caliper, ABS

DETAILS

	Frame Type	Double pipe diamond frame constructed from high-tensile steel
nm Keihin throttle bodies (2)	Rake/Trail	25/4.3 in
ctronic advance	Overall Length	85.2 in
positive neutral finder	Overall Width	33.1 in
	Overall Height	55.1 in/57.1 in (windshield down/up)
	Ground Clearance	6.7 in
lic telescopic fork with stepless	Seat Height	33.1 in
bound and preload/5.9 in	Curb Weight	476.3 lb*
laydown shock with remote	Fuel Capacity	5.5 gal
ring preload/5.7 in	Wheelbase	55.7 in
	Color Choices	Metallic Moondust Gray / Metallic Spark Black

PERFORMANCE

Front Suspension / Wheel Travel	41mm hydraulic to adjustable rebour
Rear Suspension / Wheel Travel	Single offset laydo adjustable spring



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.