²⁰²¹ VERSYS[®] 650 LT





^{MSRP} **\$9,299**



METALLIC MOONDUST GRAY/METALLIC SPARK BLACK



POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, 4 valves per cylinder parallel twin	
Displacement	649cc	
Bore x Stroke	83.0 x 60.0mm	
Compression Ratio	10.8:1	
Maximum Torque	47.0 lb-ft	
Fuel System	DFI® with 38mm Keihin throttle bodies (2)	
Ignition	TCBI with electronic advance	
Transmission	6-speed with positive neutral finder	
Final Drive	Sealed chain	

Front Tire120/70 ZR-17Rear Tire160/60 ZR-17Front BrakesDual 300mm petal-style discs with 2-piston
calipers, ABSRear BrakesSingle 250mm petal-style disc with single-
piston caliper, ABS

DETAILS

	Frame Type	Double pipe diamond frame constructed from high-tensile steel
Ceihin throttle bodies (2)	Rake/Trail	25/4.3 in
nic advance	Overall Length	85.2 in
itive neutral finder	Overall Width	33.1 in
	Overall Height	55.1 in/57.1 in (windshield down/up)
	Ground Clearance	6.7 in
elescopic fork with stepless nd and preload/5.9 in	Seat Height	33.1 in
	Curb Weight	476.3 lb. + 20 w/saddlebags & hand guards*
own shock with remote preload/5.7 in	Fuel Capacity	5.5 gal
	Wheelbase	55.7 in
	Color Choices	Metallic Moondust Gray / Metallic Spark Black

PERFORMANCE

Front Suspension / Wheel Travel	41mm hydraulic telesco adjustable rebound an
Rear Suspension / Wheel Travel	Single offset laydown s adjustable spring prelo

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.