## 2021 **VULCAN® 900 CLASSIC**





MSRP \$8,199



PEARL STORM GRAY/PEARL BLIZZARD WHITE



## **POWER**

Engine	4-stroke, 55-degree V-twin, liquid-cooled
Displacement	903cc/55.10 cu in
Bore x Stroke	88.0 x 74.2mm
Compression Ratio	9.5:1
Maximum Torque	58.2 lb-ft @ 3500 rpm
Fuel System	DFI 34mm Throttle Bodies (2), with sub- throttle valves
Ignition	TCBI w/ Electronic Advance
Transmission	5-speed with positive neutral finder
Final Drive	Kevlar-reinforced belt

## **Front Tire** 130/90-16 **Rear Tire** 180/70-15 **Front Brakes** Single 300mm hydraulic disc Single 270mm hydraulic disc **Rear Brakes**

## **DETAILS**

58.2 lb-ft @ 3500 rpm	Frame Type	Semi-double cradle, high-tensile steel
	Rake/Trail	32/6.3 in
DFI 34mm Throttle Bodies (2), with sub- throttle valves	Overall Length	97.0 in
TCBI w/ Electronic Advance	Overall Width	39.6 in
5-speed with positive neutral finder	Overall Height	41.9 in
Kevlar-reinforced belt	Ground Clearance	5.3 in
ANCE	Seat Height	26.8 in
	Curb Weight	619.6 lb*
41mm Showa telescopic fork/5.9 in	Fuel Capacity	5.3 gal
	Wheelbase	64.8 in
Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Color Choices	Pearl Storm Gray / Pearl Blizzard White

Suspension / Wheel Travel

Front

PERFORMAI

Rear Suspension / Wheel Travel

and more.

Scan with camera to view videos, key features



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.