

2021

## CONCOURS®14 ABS

**Kawasaki**  
 Let the Good Times Roll®

 MSRP  
**\$15,799**
 METALLIC SPARK BLACK


## POWER

|                       |                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------|
| Engine                | 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-cooled                                                 |
| Displacement          | 1,352cc                                                                                            |
| Bore x Stroke         | 84.0 x 61.0mm                                                                                      |
| Compression Ratio     | 10.7:1                                                                                             |
| Maximum Torque        | 100.5 lb-ft                                                                                        |
| Fuel System           | DFI® with 40mm throttle bodies (4)                                                                 |
| Ignition              | TCBI with electronic advance                                                                       |
| Transmission          | 6-speed                                                                                            |
| Final Drive           | Tetra-Lever shaft drive                                                                            |
| Electronic Rider Aids | Kawasaki Advanced Coactive-Braking Technology (K-ACT) ABS System, Kawasaki Traction Control (KTRC) |

## PERFORMANCE

|                                 |                                                                                          |
|---------------------------------|------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in |
|---------------------------------|------------------------------------------------------------------------------------------|

|                                |                                                                                                |
|--------------------------------|------------------------------------------------------------------------------------------------|
| Rear Suspension / Wheel Travel | Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in |
| Front Tire                     | 120/70 ZR-17                                                                                   |
| Rear Tire                      | 190/50 ZR-17                                                                                   |
| Front Brakes                   | Dual floating 310mm petal-style discs with four-piston calipers, ABS                           |
| Rear Brakes                    | Single 270mm petal-style disc, single-piston caliper, ABS                                      |

## DETAILS

|                  |                                      |
|------------------|--------------------------------------|
| Frame Type       | Monocoque Aluminum                   |
| Rake/Trail       | 26.0/4.4 in                          |
| Overall Length   | 87.8 in                              |
| Overall Width    | 31.1/39.4 wo/w saddlebags            |
| Overall Height   | 52.9 in/57.7 in (windshield down/up) |
| Ground Clearance | 4.9 in                               |
| Seat Height      | 32.1 in                              |
| Curb Weight      | 690.2 lb (672.5 w/o saddlebags)*     |
| Fuel Capacity    | 5.8 gal                              |
| Wheelbase        | 59.8 in                              |
| Special Features | Electrically adjusted windshield     |
| Color Choices    | Metallic Spark Black                 |

 Scan with camera  
 to view videos,  
 key features  
 and more.


\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.