## <sup>2021</sup> KLX<sup>®</sup>140R F







## Front Brakes Single 220mm petal disc with a dual-piston POWER caliper **Rear Brakes** Single 186mm petal disc with single-piston 4-stroke single, SOHC, air-cooled Engine caliper Displacement 144cc **DETAILS Bore x Stroke** 58.0 x 54.4mm Compression 9.5:1 **Frame Type** High-tensile steel, box-section perimeter Ratio 27°/4.6 in Rake/Trail 20mm Keihin carburetor **Fuel System** 78.9 in **Overall Length** Ignition Digital DC-CDI **Overall Width** 31.1 in Transmission 5-speed, return shift, with wet multi-disc manual clutch **Overall Height** 44.7 in **Final Drive** Chain Ground 12.4 in Clearance PERFORMANCE **Seat Height** 33.9 in **Curb Weight** 218.2 lb\* 33mm telescopic fork/7.5 in Front Suspension / **Fuel Capacity** 1.5 gal Wheel Travel Wheelbase 52.4 in Uni-Trak<sup>®</sup> linkage system and single shock Rear Suspension / with piggyback reservoir, 20-way rebound **Color Choices** Lime Green Wheel Travel damping and threaded preload adjustability/7.9 in Warranty 6 Months Front Tire 2.75x21 Kawasaki 12, 24, or 36 months Protection **Rear Tire** 4.10x18 Plus™

## Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

(optional)