## KLX<sup>®</sup>230R S







LIME GREEN



## **POWER**

4-stroke single, SOHC, air-cooled **Engine** 

**Displacement** 233cc

**Bore x Stroke** 67.0 x 66.0mm

Compression

Ratio

9.4:1

**Fuel System** DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

**Transmission** 6-speed, return shift with wet multi-disc

manual clutch

**Final Drive** Chain **Front Brakes** 

Single 240mm petal disc with a dual-piston

caliper

**Rear Brakes** 

Single 220mm petal disc with single-piston

**PERFORMANCE** 

37mm telescopic fork/8.7 in **Front** Suspension / **Wheel Travel** Uni-Trak® linkage system and single shock Rear with adjustable spring preload/8.8 in Suspension / **Wheel Travel Front Tire** 80/100-21

## **DETAILS**

**Frame Type** High-tensile steel, box-section perimeter

25.7° / 4.3 in Rake/Trail

80.1 in **Overall Length** 

**Overall Width** 33.1 in

**Overall Height** 46.3 in

Ground 10.8 in

Clearance

**Seat Height** 35.4 in

**Curb Weight** 253.6 lb.\*

**Fuel Capacity** 1.7 gal

Wheelbase 53.1 in

**Color Choices** Lime Green

Warranty 6 Months

Kawasaki **Protection** Plus™

(optional)

12, 24, or 36 months



**Rear Tire** 



100/100-18