KLX®230R





MSRP **\$4,399**





POWER

Engine 4-stroke single, SOHC, air-cooled

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Fuel System DFI® with 32mm Keihin throttle body

Ignition TCBI Electronic Advance

Transmission 6-speed, return shift with wet multi-disc

manual clutch

Final Drive Chain

Front Brakes

Single 240mm petal disc with a dual-piston

caliper

Rear Brakes

Single 220mm petal disc with single-piston

caliper

PERFORMANCE

Front
Suspension /
Wheel Travel

Rear
Suspension /
Suspension /
Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in

Front Tire 80/100-21

Rear Tire 100/100-18

DETAILS

Frame Type High-tensile steel, box-section perimeter

Rake/Trail 26.5°/4.4 in

Overall Length 80.5 in

Overall Width 33.1 in

Overall Height 47.2 in

Ground 11.8 in Clearance

Seat Height 36.4 in

Curb Weight 253.6 lb.*

Fuel Capacity 1.7 gal

Wheelbase 53.5 in

Color Choices Lime Green

Warranty 6 Months

Kawasaki 12, 24, or 36 months Protection Plus™





(optional)