²⁰²¹ KLX®300







POWER Engine Displacement Bore x Stroke	4-stroke single, DOHC, liquid-cooled 292cc 78.0 x 61.2mm	Rear Tire Front Brakes Rear Brakes	4.60 x 18 Single 250mm petal disc with a dual- piston caliper Single 240mm petal disc with single- piston caliper
Compression Ratio	11.1:1	DETAILS	
Fuel System Ignition Transmission	DFI® with 34mm Keihin throttle body CDI 6-speed, return shift with wet multi-disc manual clutch	Frame Type Rake/Trail Overall Length Overall Width	High-tensile steel, box-section perimeter 26.7°/4.2 in 86.6 in 32.3 in
Final Drive	Chain	Overall Height	47.4 in
PERFORMANCE		Ground Clearance	10.8 in.
Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping/10.0 in	Seat Height Curb Weight	35.2 in 302.1 lb*
Rear Suspension / Wheel Travel	Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/9.1 in	Fuel Capacity Wheelbase Color Choices	2.0 gal 56.7 in Lime Green, Fragment Camo Gray

Front Tire

Scan with camera

to view videos,

key features

and more.

3.00 x 21

m 1

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.