

# 2021 KX™100

**Kawasaki**  
Let the Good Times Roll®



MSRP  
**\$4,649**

 LIME GREEN



## POWER

|                          |                                                          |
|--------------------------|----------------------------------------------------------|
| <b>Engine</b>            | 2-stroke single with exhaust power valve, liquid-cooled  |
| <b>Displacement</b>      | 99cc                                                     |
| <b>Bore x Stroke</b>     | 52.5 x 45.8mm                                            |
| <b>Compression Ratio</b> | 10.2:1 (low speed) - 8.7:1 (high speed)                  |
| <b>Fuel System</b>       | 28mm Keihin carburetor                                   |
| <b>Ignition</b>          | CDI with digital advance                                 |
| <b>Transmission</b>      | 6-speed, return shift, with wet multi-disc manual clutch |
| <b>Final Drive</b>       | Chain                                                    |

|                     |                                                    |
|---------------------|----------------------------------------------------|
| <b>Front Tire</b>   | 70/100-19                                          |
| <b>Rear Tire</b>    | 90/100-16                                          |
| <b>Front Brakes</b> | Single 220mm petal disc with dual-piston caliper   |
| <b>Rear Brakes</b>  | Single 184mm petal disc with single-piston caliper |

## PERFORMANCE

|                                        |                                                                                                                                                |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Front Suspension / Wheel Travel</b> | 36mm inverted telescopic cartridge fork with 20-way compression damping/10.8 in                                                                |
| <b>Rear Suspension / Wheel Travel</b>  | Uni-Trak® gas charged shock with piggyback reservoir with 24-way compression and 21-way rebound damping plus adjustable spring preload/10.8 in |

## DETAILS

|                         |                                                          |
|-------------------------|----------------------------------------------------------|
| <b>Frame Type</b>       | High-tensile steel perimeter design with subframe member |
| <b>Rake/Trail</b>       | 29° / 4.3 in                                             |
| <b>Overall Length</b>   | 75.6 in                                                  |
| <b>Overall Width</b>    | 30.1 in                                                  |
| <b>Overall Height</b>   | 45.3 in                                                  |
| <b>Ground Clearance</b> | 13.0 in                                                  |
| <b>Seat Height</b>      | 34.3 in                                                  |
| <b>Curb Weight</b>      | 169.7 lb*                                                |
| <b>Fuel Capacity</b>    | 1.32 gal                                                 |
| <b>Wheelbase</b>        | 51.6 in                                                  |
| <b>Color Choices</b>    | Lime Green                                               |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.