²⁰²¹ **KX[™]250X**







80/100-21

110/100-18

single-piston caliper

Single semi-floating 270mm Braking®

Single 240mm Braking® petal disc with

petal disc with dual-piston caliper

POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

DETAILS

Front Tire

Rear Tire

Front Brakes

Rear Brakes

Frame Type	Aluminum perimeter
Rake/Trail	27.8/4.8 in
Overall Length	85.4 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	230.1 lb without fuel / 240.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Color Choices	Lime Green

PERFORMANCE

Front
Suspension /
Wheel Travel48mm inverted telescopic coil spring fork
with 23-way compression damping and
20-way rebound damping /12.4 inRear
Suspension /
Wheel TravelUni-Trak® with dual-range (2.25 turns high
speed/21-way low-speed) compression
damping, 38-way rebound damping and
adjustable preload/12.4 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.