²⁰²¹ **KX[™]450**







POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	449cc
Bore x Stroke	96.0 x 62.1mm
Compression Ratio	12.5:1
Fuel System	DFI® with 44mm Keihin throttle body
Ignition	Digital CDI with 3 Coupler Options
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation
Final Drive	Chain

PERFORMANCE

Front
Suspension /
Wheel Travel49mm inverted telescopic coil-spring fork
with 16-way compression damping and 16-
way rebound damping/12.0 inRear
Suspension /
Wheel TravelUni-Trak® gas charged shock with
piggyback reservoir with dual-range (4
turns stepless high speed/19-way low-
speed) compression damping, 22-way
rebound damping and adjustable
preload/12.1 in

Front Tire	80/100-21
Rear Tire	120/80-19
Front Brakes	Single semi-floating 270mm Braking® petal disc with dual-piston caliper
Rear Brakes	Single 250mm Braking® petal disc with single-piston caliper

DETAILS

	Frame Type	Aluminum perimeter
	Rake/Trail	27.6°/4.8 in
	Overall Length	86.0 in
	Overall Width	32.3 in
i	Overall Height	49.8 in
_	Ground Clearance	13.4 in
	Seat Height	37.6 in
	Curb Weight	232.7 lb without fuel / 242.9 lb*
	Fuel Capacity	1.64 gal
	Wheelbase	58.5 in
	Color Choices	Lime Green



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.