²⁰²¹ **KX**[™]65







80/100-12

POWER

		Front Brakes	Single 180mm disc with single-piston
Engine	2-stroke single, liquid-cooled		caliper
Displacement	64cc	Rear Brakes	Single 180mm disc with single-piston caliper
Bore x Stroke	45.5 x 41.6mm		
Compression Ratio	8.4:1	DETAILS	
Fuel System	24mm Mikuni carburetor	Frame Type	High-tensile steel semi-double cradle
Ignition	CDI with digital advance	Rake/Trail	27°/2.4 in
Transmission	6-speed, return shift, with wet multi-disc	Overall Length	62.6 in
Tulioniosion	manual clutch	Overall Width	29.9 in
Final Drive	Chain	Overall Height	37.6 in
PERFORMANCE		Ground Clearance	12.0 in
Front	33mm leading axle telescopic fork with	Seat Height	29.9 in
Suspension / Wheel Travel	4-way rebound damping/8.3 in	Curb Weight	132.2 lb*

Rear Tire

Rear Suspension / Wheel Travel

Front Tire

60/100-14

Uni-Trak® single shock system with 4way rebound damping and fully adjustable spring preload/9.4 in

> *Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Fuel Capacity

Color Choices

Wheelbase

1.0 gal

44.1 in

Lime Green

Scan with camera to view videos, key features and more.

