## **MULE PRO-DXT™ DIESEL**





\$14,399



SUPER BLACK



## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement 993cc

**Maximum Torque** 38.3 lb-ft @ 2400 rpm

**Bore x Stroke** 2.91x3.03 in

**Compression Ratio** 23.5:1

**Fuel System** Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 55 amp

(max)

**Ground Clearance** 

**Fuel Capacity** 

**Turning Radius** 

**Cargo Bed** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

**Payload Capacity** 

**Seating Capacity** 

**Towing Capacity** 

Lighting

10.2 in

7.9 gal

16.0 ft

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

person)

1581 lb

3-person (1 row), 6 person (2 row)

1000 lb (3-person)350 lb (6-person)

2000 lb

(2) Halogen headlights.

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Dual Disc, 1 piston caliper

Rear Suspension / **Wheel Travel** 

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12 **Rear Tires** 26x11.00-12

Rack-and-pinion, Tilt steering Steering

**Front Brakes** Dual Disc, 2 piston caliper

Independent, Mechanical Disc **Park Brake Type** 

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

**Curb Weight** 1922.8 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and

parking indicators, seatbelt reminder lamps

**Wheel Type** Steel

**Color Choices** Super Black

Scan with camera to view videos, key features and more.

**Rear Brakes** 



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471