## **MULE PRO-FX™**





MSRP **\$12,199** 



SUPER BLACK



## **POWER**

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Ye

Alternator Output 75 amp

(max)

Ground Clearance 10.4 in

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

. .

**Payload Capacity** 

**Seating Capacity** 

Towing Capacity

Lighting

1616 lb

2000 lb

(2) Halogen headlights.

54.1 x 53.3 x 11.0 in

1000 lb (600 lb for California models)

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/8.7 in

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 26x9.00-12, radial

Rear Tires 26x11.00-12, radial

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Rack-and-pinion

Park Brake Type Independent, Mechanical Disc

## **DETAILS**

Overall Length 133.3 in

Overall Width 64.0 in

Overall Height 77.4 in

Curb Weight 1816.9 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps

Wheel Type Steel

Color Choices Super Black

Scan with camera to view videos, key features and more.

Steering



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.