
2021 **MULE PRO-FXT[™] EPS**







10.2 in

7.9 gal

16.0 ft

person)

models)

1616 lb

2000 lb

133.3 in

64.0 in

77 6 in

42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-

3-person (1 row), 6 person (2 row)

(2) Halogen headlights.

1000 lb (3-person)350 lb (6-person)(600 lb for California

POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Maximum Torque	48.0 lb-ft @ 3500 rpm
Bore x Stroke	2.83x2.62 in
Compression Ratio	9.5:1
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

CAPABILITY

		Overall Height	//.0 [[]
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Curb Weight	1911.7 lb*
Rear Suspension /	Double wishbone/8.5 (L) /8.7 (R) in	Wheelbase	92.3 in
Wheel Travel		Instruments	Multi-function display includes digital speedometer.
Front Tires	26x9.00-12, radial		fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning
Rear Tires	26x11.00-12, radial		indicator, oil pressure warning indicator, fuel injection
Steering	Electric Power Steering (EPS), Tilt steering		warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual Disc, 2 piston caliper		
	the set of	Wheel Type	Steel
Rear Brakes	Dual Disc, 1 piston caliper		
Park Brake Type	Independent, Mechanical Disc	Color Choices	Timberline Green, Bright White

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Ground Clearance

Fuel Capacity

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

DETAILS

Overall Length

Overall Width

orall Hoight

Cargo Bed Dimensions (LxWxH)

Capacity

Lighting

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE[™] side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

