MULE PRO-MX™ EPS LE





\$12,599

SUPER BLACK



FIRECRACKER RED



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, Mechanical Disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb (600 lb California models)

33.4 x 44.1 x 9.1 in

Cargo Bed Load Capacity

Payload Capacity

Towing Capacity

1200 lb

Seating Capacity

1500 lb

(2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Wheel Travel

Steering

Double wishbone/9.1 in

Front Tires 25x10.00-12, radial

Rear Tires 25x10.00-12, radial

Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper **DETAILS**

Lighting

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1594.2 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Wheel Type Alloy

Color Choices Firecracker Red, Super Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.