## **MULE PRO-MX™ EPS LE**





## \$12,599



SUPER BLACK



FIRECRACKER RED



## **POWER**

**Engine** 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement

**Maximum Torque** 42.7 lb-ft @ 5000 rpm

102.0 x 85.0 mm Bore x Stroke

**Compression Ratio** 10.3:1

**Fuel System** DFI® with 44mm throttle body

Continuously Variable Transmission (CVT) with centrifugal **Transmission** 

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 35.7 amp

(max)

**Ground Clearance** 10.6 in

**Fuel Capacity** 9.5 gal **Turning Radius** 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

**Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

699 lb (600 lb California models)

**Payload Capacity** 1200 lb

**Seating Capacity** 

**Towing Capacity** 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

## CAPABILITY

Front Suspension / Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/8.6 in

**Front Tires** 

25x10.00-12, radial

**Rear Tires** 

25x10.00-12, radial

Steering Front Brakes

**Rear Brakes** 

**Park Brake Type** 

Double wishbone/9.1 in

Electric Power Steering (EPS), Tilt steering

Dual Disc, 2 piston caliper

Dual Disc, 1 piston caliper

Independent, Mechanical Disc

**DETAILS** 

**Overall Length** 

110.0 in

**Overall Width** 60.0 in

**Overall Height** 75.8 in

**Curb Weight** 1594.2 lb\*

Wheelbase 78.9 in

Multi-function display includes digital speedometer, fuel Instruments gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Alloy

**Color Choices** Firecracker Red, Super Black

Warranty Kawasaki Strong 3-Year Limited Warranty

**Kawasaki Protection** 12, 24 or 36 months

Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.