

2021

TERYX4™ S CAMO

Kawasaki

Let the Good Times Roll®



MSRP

\$16,999

 REALTREE XTRA® GREEN CAMO



POWER

Engine	4-stroke, SOHC, 4-valve V-twin, liquid-cooled
Displacement	783cc
Maximum Torque	47.0 lb-ft@ 5500 rpm
Bore x Stroke	85.0 x 69.0mm
Compression Ratio	10.7:1
Fuel System	DFI® with two 36mm Mikuni throttle bodies
Ignition	TCBI with electronic advance
Starting System	Electric
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with locking front differential, shaft
Engine Braking	Yes

Turning Radius	17.7 ft.
Cargo Bed Dimensions (LxWxH)	17.9 x 47.6 x 8.7 in
Cargo Bed Load Capacity	249 lb
Payload Capacity	1096 lb
Seating Capacity	4
Towing Capacity	1300 lb
Lighting	(4) LED headlights, (2) LED taillights, LED stoplight
Standard Ground Clearance/Maximum Ground Clearance†	11.2 in / 12.2 in

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping / 10.7 in.
Rear Suspension / Wheel Travel	Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression damping / 10.0 in.
Front Tires	Maxxis 27 x 9-14
Rear Tires	Maxxis 27 x 11-14
Steering	Electric Power Steering (EPS) / rack-and-pinion
Front Brakes	Dual hydraulic discs with two-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc
Fuel Capacity	7.9 gal

DETAILS

Frame	Steel Tube Double-X Reinforcement
Overall Length	125.4 in
Overall Width	62.6 in
Overall Height	80.5 in
Curb Weight	1642.7 lb*
Wheelbase	88.2 in
Instruments	Multi-function digital meter with speedometer, fuel gauge, clock, hour meter, odometer, dual trip meter and parking-brake indicator, R/N/P/4WD, water temp and low-oil-pressure indicators
Wheel Type	Alloy
Color Choices	Realtree Xtra® Green Camo
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, or 36 months

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
†Maximum ground clearance is measured at maximum pre-load suspension setting.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.