
JET SKI[®] STX[®] 160X











POWER

		_
Engine	4-stroke, DOHC, four valves per cylinder, 4-cylinder inline	P
Displacement	1,498cc	Lu
Bore x Stroke	83.0 x 69.2mm	Со
Compression	10.6:1	Oil
Ratio		Fu
Induction	Naturally aspirated	Lo
Maximum Boost	N/A	Sto Ca
Cooling System	Inducted water	D
Fuel System	DFI® with 60mm throttle body	Ον
Ignition	TCBI with digital advance	Ov
Starting System	Electric	Ov
Propulsion	148mm jet pump, axial-flow, single stage	Cu
System Impeller	3-blade, oval-edge stainless steel	Se Ca

PERFORMANCE

Thrust

Lubrication	Semi-dry sump system
Coupling	Direct drive from engine
Oil Capacity	5.8 qt.
Fuel Capacity	20.6 gal.
Load Capacity	496 lb.
Storage Capacity	35.0 gal.

957 lb

DETAILS

Overall Length	124.1 in
Overall Width	46.5 in.
Overall Height	45.4 in.
Curb Weight	864.4 lb.*
Seating Capacity	3
Color Choices	Ebony/Lime Green





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.