2022 **VULCAN® 900 CLASSIC LT**





^{MSRP} **\$9,499**



PEARL ROBOTIC WHITE/PEARL NIGHTSHADE TEAL



POWER

Engine	4-stroke, 55-degree V-twin, liquid-cooled		
Displacement	903cc/55.10 cu in		
Bore x Stroke	88.0 x 74.2mm		
Compression Ratio	9.5:1		
Maximum Torque	58.2 lb-ft @ 3500 rpm		
Fuel System	DFI 34mm Throttle Bodies (2), with sub- throttle valves		
Ignition	TCBI w/ Electronic Advance		
Transmission	5-speed with positive neutral finder		
Final Drive	Kevlar-reinforced belt		

Front Tire 130/90-16 **Rear Tire** 180/70-15 **Front Brakes** Single 300mm hydraulic disc Single 270mm hydraulic disc **Rear Brakes**

DETAILS

Ratio				
Maximum	58.2 lb-ft @ 3500 rpm	Frame Type	Semi-double cradle, high-tensile steel	
Torque		Rake/Trail	32/6.3 in	
Fuel System	DFI 34mm Throttle Bodies (2), with sub- throttle valves	Overall Length	97.0 in	
Ignition	TCBI w/ Electronic Advance	Overall Width	39.6 in	
Transmission	5-speed with positive neutral finder	Overall Height	58.3 in	
Final Drive	Kevlar-reinforced belt	Ground Clearance	5.3 in	
PERFORMANCE		Seat Height	26.8 in	
		Curb Weight	657.1 lb*	
Front Suspension /	41mm Showa telescopic fork/5.9 in	Fuel Capacity	5.3 gal	
Wheel Travel		Wheelbase	64.8 in	
Rear Suspension / Wheel Travel	Uni-Trak® swingarm, 7-way adjustable spring preload/4.1 in	Color Choices	Pearl Robotic White/Pearl Nightshade Teal	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.