## <sup>2022</sup> KLX<sup>®</sup>230 SE







POWER		Front Brakes	Single 240mm petal disc with a dual-piston caliper
Engine	4-stroke single, SOHC, air-cooled	Rear Brakes	Single 220mm petal disc with single-piston caliper
Displacement	233cc		
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	DFI® with 32mm Keihin throttle body	Rake/Trail	27.5°/4.6 in
Ignition	TCBI Electronic Advance	Overall Length	82.9 in.
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Width	32.9 in.
		Overall Height	45.9 in.
Final Drive	Chain	Ground Clearance	10.4 in.
PERFORMANCE		Seat Height	34.8 in.
Front	37mm telescopic fork/8.7 in	Curb Weight	291.1 lb. / 293.3 lb. CA model
Suspension / Wheel Travel		Fuel Capacity	2.0 gal.
Rear	Uni-Trak <sup>®</sup> linkage system and single shock	Wheelbase	54.3 in.
Suspension / Wheel Travel	with adjustable spring preload/8.8 in	Color Choices	Firecracker Red, Oriental Blue
Front Tire	2.75 x 21	Warranty	12 Months
Rear Tire	4.10 x 18	Kawasaki Protection Plus™ (optional)	12, 24, or 36 months



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.