
## <sup>2022</sup> KLX®300SM







## POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	292cc
Bore x Stroke	78.0 x 61.2mm
Compression Ratio	11.1:1
Fuel System	DFI® with 34mm Keihin throttle body
Ignition	CDI
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted cartridge fork with adjustable compression damping/9.1 in
Rear Suspension / Wheel Travel	Uni-Trak® gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/8.1 in

Front Tire	110/70-17
Rear Tire	130/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper
Rear Brakes	Single 240mm petal disc with single-piston caliper

## **DETAILS**

Frame Type	Semi Double Cradle
Rake/Trail	25.0°/2.8 in
Overall Length	86.4 in
Overall Width	31.1 in
Overall Height	45.1 in
Ground Clearance	9.3 in
Seat Height	33.9 in
Curb Weight	304.3 lb*
Fuel Capacity	2.0 gal
Wheelbase	56.5 in
Color Choices	Lime Green/Ebony, Ebony



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.