²⁰²² **KX[™]450SR**







Front Brakes Single semi-floating 270mm Braking® petal POWER disc with dual-piston caliper **Rear Brakes** Single 250mm Braking® petal disc with single-Engine 4-stroke single, DOHC, liquid-cooled piston caliper Displacement 449cc **DETAILS Bore x Stroke** 96.0 x 62.1mm Compression 12.5:1 Aluminum perimeter **Frame Type** Ratio 27.4°/4.8 in Rake/Trail **Fuel System** DFI® with 44mm Keihin throttle body **Overall Length** 86.0 in Ignition Digital CDI with 3 Coupler Options **Overall Width** 32.3 in Transmission 5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation **Overall Height** 49.8 in **Final Drive** Chain Ground 13.4 in Clearance PERFORMANCE **Seat Height** 37.6 in b*

Front	12.4 in	Curb Weight	232.7 lb without fuel / 242.9 lb
Suspension / Wheel Travel		Fuel Capacity	1.64 gal
Rear	12.1 in	Wheelbase	58.5 in
Suspension / Wheel Travel		Color Choices	Lime Green
Front Tire	80/100-21	Warranty	Not Available
Rear Tire	120/80-19	Kawasaki Protection Plus™ (optional)	Not Available



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.