## <sup>2022</sup> MULE PRO-DXT<sup>™</sup> EPS DIESEL FE





<sup>MSRP</sup> **\$17,699** 

BRIGHT WHITE



## POWER

Engine	4-stroke, 3-cylinder, OHV, liquid-cooled, diesel
Displacement	993cc
Maximum Torque	38.3 lb-ft @ 2400 rpm
Bore x Stroke	2.91x3.03 in
<b>Compression Ratio</b>	23.5:1
Fuel System	Bosch in-line injection pump
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	55 amp

## CAPABILITY

Front Suspension / Wheel Travel	Double wishbone/8.7 in	Curb We
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) /8.7 (R) in	Wheelba
		Instrume
Front Tires	26x9.00-12	
Rear Tires	26x11.00-12	
Steering	Electric Power Steering (EPS), Tilt steering	
Front Brakes	Dual Disc, 2 piston caliper	Wheel Ty
Rear Brakes	Dual Disc, 1 piston caliper	Color Ch
Park Brake Type	Independent, Mechanical Disc	

Ground Clearance	10.2 in
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6- person)
Cargo Bed Load Capacity	999 lb (3-person), 350 lb (6-person)
Payload Capacity	1581 lb
Seating Capacity	3-person (1 row), 6 person (2 row)
Towing Capacity	2000 lb
Lighting	(2) Halogen headlights.

## DETAILS

Overall Length	133.3 in
Overall Width	64.0 in
 Overall Height	79.5 in
Curb Weight	1964.7 lb*
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Wheel Type	Steel
Color Choices	Bright White

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE<sup>TM</sup> PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

