2022 **MULE PRO-FX[™] EPS LE**





POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Maximum Torque	48.0 lb-ft @ 3500 rpm
Bore x Stroke	2.83x2.62 in
Compression Ratio	9.5:1
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

CAPABILITY

		Overall Height	79.7 in
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Curb Weight	1832.4 lb*
Rear Suspension /	Double wishbone/8.5 (L) /8.7 (R) in	Wheelbase	92.3 in
Wheel Travel Front Tires	26x9.00-12, radial	Instruments	Multi-function display incluc fuel gauge, odometer, hour r
Rear Tires	26x11.00-12, radial		meters, 2WD/4WD indicator, indicator, oil pressure warnin warning indicator, CVT and E
Steering	Electric Power Steering (EPS), Tilt steering		neutral, reverse and parking reminder lamps
Front Brakes	Dual Disc, 2 piston caliper	Wheel Ture	·
Rear Brakes	Dual Disc, 1 piston caliper	Wheel Type	Alloy
Park Brake Type	Independent, Mechanical Disc	Color Choices	Firecracker Red

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULETM PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULETM side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.



awas Let the Good Times Roll

Ground Clearance	10.4 in
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Cargo Bed Load Capacity	999 lb (600.0 lb for California models)
Payload Capacity	1616.3 lb (1263.5 for California models)
Seating Capacity	3
Towing Capacity	2000 lb
Lighting	(2) Halogen headlights. (2) LED headlights

DETAILS

F

Overall Length	133.3 in
Overall Width	64.0 in
Overall Height	79.7 in
Curb Weight	1832.4 lb*
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Wheel Type	Alloy
Color Choices	Firecracker Red