MULE PRO-FXR™





\$15,999



METALLIC CARBON GRAY



POWER

Engine 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

Maximum Torque 48.0 lb-ft @ 3500 rpm

Bore x Stroke 2.83x2.62 in

Compression Ratio 9.5:1

Fuel System DFI® with 34mm throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 75 amp

(max)

Ground Clearance 10.8 in

Fuel Capacity 7.9 gal

Turning Radius 14.0 ft

Cargo Bed Dimensions (LxWxH)

999 lb (600.0 lb for California models)

37.6 x 53.3 x 11.0 in

Cargo Bed Load Capacity

Payload Capacity

1616.3 lb (1263.5 for California models)

Seating Capacity

Towing Capacity

2000 lb

Lighting

(2) Halogen headlights. (2) LED headlights

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone/8.7 in

Rear Suspension / **Wheel Travel**

Double wishbone/8.5 (L) /8.7 (R) in

Front Tires 27x9.00-12, radial

Rear Tires 27x11.00-12, radial

Electric Power Steering (EPS), Tilt steering Steering

Front Brakes Dual Disc, 2 piston caliper

Rear Brakes Dual Disc, 1 piston caliper

Independent, Mechanical Disc **Park Brake Type**

DETAILS

Overall Length 121.5 in

Overall Width 64.0 in

Overall Height 77.2 in

Curb Weight 1768.4 lb*

Wheelbase 79.7 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

Wheel Type Alloy

Color Choices Metallic Carbon Gray

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471