## **MULE PRO-FXT™ EPS**





\$16,599



**BRIGHT WHITE** 



TIMBERLINE GREEN



## **POWER**

**Engine** 4-stroke, 3-cylinder, DOHC, liquid-cooled, gas

Displacement 812cc

**Maximum Torque** 48.0 lb-ft @ 3500 rpm

**Bore x Stroke** 2.83x2.62 in

**Compression Ratio** 9.5:1

**Fuel System** DFI® with 34mm throttle body

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** 

**Alternator Output** 75 amp

(max)

**Ground Clearance** 

**Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

**Cargo Bed** 

**Dimensions (LxWxH)** 

42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6-

999 lb (3-person), 350 lb (6-person), (348 lb for California

person)

10.2 in

**Cargo Bed Load** 

Capacity

models)

**Payload Capacity** 

1616.3 lb (1263.5 for California models) 3-person (1 row), 6 person (2 row)

**Seating Capacity Towing Capacity** 

2000 lb

Lighting

(2) Halogen headlights.

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone/8.7 in

Rear Suspension /

Double wishbone/8.5 (L) /8.7 (R) in

**Wheel Travel Front Tires** 

26x9.00-12, radial

**Rear Tires** 

26x11.00-12, radial

Steering

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Dual Disc, 2 piston caliper

**Rear Brakes** 

Dual Disc, 1 piston caliper

**Park Brake Type** 

Independent, Mechanical Disc

## **DETAILS**

**Overall Length** 133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

**Curb Weight** 1911.7 lb\*

Wheelbase 92.3 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt

reminder lamps

**Wheel Type** Steel

**Color Choices** 

Timberline Green, Bright White

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE SX™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.