## **MULE PRO-MX™ EPS CAMO**





MSRP **\$13,549** 



TRUETIMBER® HTC GREEN



## **POWER**

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

**Alternator Output** 

(max)

35.7 amp

## **CAPABILITY**

Front Suspension / Wheel Travel

Double wishbone/8.6 in

Rear Suspension /

Double wishbone/9.1 in

Wheel Travel
Front Tires

25x8.00-12, radial 25x10.00-12, radial

Rear Tires

Electric Power Steering (EPS), Tilt steering

**Front Brakes** 

Steering

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Park Brake Type Independent, Mechanical Disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

699 lb (600 lb California models)

Cargo Bed Load Capacity

capacity

Payload Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

33.4 x 44.1 x 9.1 in

## **DETAILS**

Overall Length 110.0 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1598.6 lb\*

Wheelbase 78.9 in

**Instruments** Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Wheel Type Steel

Color Choices TrueTimber® HTC Green

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.