MULE PRO-MX™ EPS LE





MSRP **\$13,499**



SUPER BLACK



POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, Mechanical Disc

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Payload Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

699 lb (600 lb California models)

CAPABILITY

Front Suspension / Double wishbone / 8.6 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

 Front Tires
 25x8.00-12, radial

 Rear Tires
 25x10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper
Rear Brakes Dual Disc, 1 piston caliper

Overall Height

DETAILS

Overall Length

Overall Width

75.8 in

110.0 in

60.0 in

Curb Weight 1594.2 lb*

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

Wheel Type Alloy

Color Choices Super Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.