2022 NINJA[®] 400









POWER		Front Brakes	Single 310mm semi-floating petal-type disc with 2-piston calipers and ABS
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Rear Brakes	Single 220mm petal-type disc with single-piston caliper and ABS
Displacement	399сс		
Bore x Stroke	70.0 x 51.8mm	DETAILS	
Compression Ratio	11.5:1	Frame Type	Trellis, high-tensile steel
Fuel System	DFI® with dual 32mm throttle bodies	Rake/Trail	24.7°/3.6 in.
Ignition	TCBI w/digital advance	Overall Length	78.3 in
Transmission	6-speed	Overall Width	28 in
Final Drive	Sealed chain	Overall Height	44.1 in
Electronic Rider Aids	ABS	Ground Clearance	5.5 in
		Seat Height	30.9 in
PERFORMANCE		Curb Weight	366*
Front	41mm hydraulic telescopic fork/4.7 in	Fuel Capacity	3.7 gal
Suspension / Wheel Travel		Wheelbase	53.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in	Color Choices	Metallic Matte Twilight Blue/Metallic Graphite Gray, Metallic Carbon Gray/Metallic Flat Spark Black
Front Tire	110/70-17	Warranty	12 Month Limited Warranty

Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.7 in		
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in		
Front Tire	110/70-17		
Rear Tire	150/60-17		

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

12, 24, 36 or 48 months

Kawasaki

Protection Plus™ (optional)

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

