2022 NINJA H2[®] SX SE





^{MSRP} **\$27,500**



EMERALD BLAZED GREEN/METALLIC DIABLO BLACK/ METALLIC GRAPHITE GRAY



POWER

| Engine | Liquid -cooled, 4-stroke, In-Line Four, DOHC, 16-valve |
|--------------------------|--|
| Displacement | 998cc |
| Bore x Stroke | 76.0 x 55.0mm |
| Compression Ratio | 11.2:1 |
| Maximum Torque | 101.0 lb-ft |
| Fuel System | DFI® with 40mm throttle bodies; Kawasaki Supercharger |
| Ignition | TCBI w/Digital Advance |
| Transmission | 6-speed, Manual, Return Shift, Dog Ring |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Advanced Rider Assistance Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC). Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa's Skyhook Technology (KECS), Power Modes, Integrated Riding Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Traction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (dual direction), LED Cornering Lights, Grip Heaters, TPMS |

Wheel Travelreservoir, KECS-controlled compression and rebound
damping electronically-adjustable spring preload/5.5 inFront Tire120/70 ZR17 (58W)Rear Tire190/55 ZR17 (75W)Front BrakesDual radial-mount, opposed 4-piston Brembo Stylema®
monobloc calipers, dual semi-floating 320mm discs,
KIBS ABSRear BrakesOpposed 2-piston calipers, single 250mm disc, KIBS ABS

New Uni-Trak[®], BFRC gas charged shock with piggyback

DETAILS

Rear Suspension /

| Frame Type | Trellis, high-tensile steel, with swingarm mounting plate |
|------------------|---|
| Rake/Trail | 24.7°/4.1 in |
| Overall Length | 85.6 in |
| Overall Width | 31.1 in |
| Overall Height | 49.6 in |
| Ground Clearance | 5.1 in |
| Seat Height | 32.9 in |
| Curb Weight | 590.9 lb |
| Fuel Capacity | 5.0 gal |
| Wheelbase | 58.3 in |
| Special Features | 6.5" Full-Color TFT Instrumentation, Kawasaki SPIN infotainment app, All-LED lighting, KIPASS, Highly Durable Paint |
| Color Choices | Emerald Blazed Green/Metallic Diablo Black/Metallic Graphite Gray |
| | |

PERFORMANCE

Front Suspension / Wheel Travel 43mm inverted fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.