
## JET SKI<sup>®</sup> STX<sup>®</sup> 160X











## POWER

		U	
Engine	4-stroke, DOHC, four valves per cylinder, 4- cylinder inline	F	
Displacement	1,498cc	L	
Bore x Stroke	83.0 x 69.2mm	S C	
Compression Ratio	10.6:1	Ι	
Induction	Naturally aspirated	0	
Maximum Boost	N/A		
<b>Cooling System</b>	Inducted water	0	
Fuel System	DFI® with 60mm throttle body	0	
Ignition	TCBI with Digital Advance	C	
Starting System	Electric	S C	
Propulsion System	148mm jet pump, axial-flow, single stage	C	
Impeller	3-blade, oval-edge stainless steel	N	
Thrust	957 lb	K P	
PERFORMANCE			

Coupling	Direct drive from engine
Oil Capacity	5.8 qt
Fuel Capacity	20.6 gal
Load Capacity	496 lb
Storage Capacity	35.0 gal

## DETAILS

Overall Length	124.1 in
Overall Width	46.5 in
Overall Height	45.4 in
Curb Weight	864.4 lb*
Seating Capacity	3
Color Choices	Ebony/Lime Green
Warranty	12 Month Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24, 36, or 48 months

## Lubrication

Semi-dry sump system



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a USCG-approved personal flotation device, eyewear, gloves, footwear, and a wet suit or clothing that provides equivalent protection (board shorts with neoprene liner). Never ride under the influence of drugs or alcohol. Respect the rights of shoreline residents and other marine recreationists. Boat smart from the start. Take a Boating Safety course; for more information visit www.USCGBoating.org. Jet Ski watercraft are inboard powerboats and their use is subject to all applicable federal, state, and local boating laws. Read Owner's Manual and all on-product warnings. @2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.