

2023

ELEKTRODE®



MSRP

\$1,099



POWER

Motor Type	Air-cooled, brushless, in-wheel
Power Modes	3 modes (High / Mid / Low)
Max Speed by Mode - H / M / L	13 mph / 7.5 mph / 5 mph
Battery Type	Lithium-ion (in-frame)
Battery Voltage/ Capacity	36 V 5.1 Ah (187.2 Wh)
Battery Charge Time	2.5 hours (approx)
Drive System	Direct hub motor
Battery Rated Output	250 Watts
Battery Running Time	150+ minutes
Maximum Battery Charge Cycles	500 (after which 80% of original charge capacity)

PERFORMANCE

Frame Type	Aluminum
Front Suspension/ Wheel Travel	28.8 mm steel fork / rigid
Rear Suspension/ Wheel Travel	Rigid
Front Tire	16 x 2.125
Rear Tire	16 x 2.125

Front Brakes	-
Rear Brakes	160 mm mechanical disc
Handlebar Clamp Size	22.2mm
Steering Stem Size	28.6mm
Seat Post Size	27.2mm

DETAILS

Rake & Trail	25 deg / 2.95 in (75mm)
Overall Length	48.6 in (1,235mm)
Overall Width	22.9 in (582mm)
Overall Height	30.2 in (767mm)
Ground Clearance	5.5 in (139mm)
Seat Height	16.1-20.5 in (410-520mm)
Wheelbase	32.75 in (832mm)
Curb Weight	31.97 lb (14.5 kg)
Color Choices	Lime Green
Appropriate Rider's Age	3-8 years old
Rider Weight (max)	99.5 lb (45 kg)
Footrest	Yes (footpeg, foldable)
Charging power source	110-V Single Phase AC (Home)
Charging connector	Under the frame
Number plate	STD

Scan with camera
to view videos,
key features
and more.



*Running time varies based on battery age, charge and the number of charge cycles it has had, rider weight, speed and riding conditions.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection, gloves and elbow pads, kneepads, and proper apparel.
Always abide by local rules and regulations. Never use near motor vehicles, at night or when visibility is limited. Adhere to the maintenance schedule in your
Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.