2023 **KLR®650**







POWER		Front Brakes	Single 300mm disc with 2-piston calipers (and ABS)
Engine	4-Stroke, single cylinder, DOHC	Rear Brakes	Single 240mm disc with single-piston caliper (and ABS)
Displacement Bore x Stroke	652cc 100.0 x 83.0mm	DETAILS	
Compression Ratio	9.8:1	Frame Type	Tubular, semi-double cradle
Maximum Torque	39.1 lbft. @ 4,500rpm	Rake/Trail	30.0°/4.8 in
Fuel System	DFI® with 40mm throttle body	Overall Length Overall Width	89.8 in 38.2 in
Ignition	CDI	Overall Height	57.7/56.3 in (screen hi/lo)
Transmission	5-speed, return shift with wet multi-disc manual clutch	Ground	8.3 in
Final Drive	Sealed chain	Clearance	34.3 in
Electronic Rider Aids	Anti-lock Brake System (ABS)	Seat Height Curb Weight	460.6 lb* (ABS), 456.2 lb* (non-ABS)
PERFORMANCE		Fuel Capacity	6.1 gal

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork/ 7.9 in	Color Choices
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/ 7.3 in	Warranty Kawasaki Protection Plus™ (optional)
Front Tire	90/90-21	
Rear Tire	130/80-17	

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.

Wheelbase

60.6 in

Yellow, Candy Lime Green

12 Month Limited Warranty

12, 24, or 36 months

Pearl Storm Gray / Pearl Storm Gray, Pearl Solar

Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

