²⁰²³ **KLX[®]230R**







100/100-18

11.8 in

POWER

		Front Brakes	Single 240mm petal disc with a dual-	
Engine	4-stroke single, SOHC, air-cooled		piston caliper	
Displacement	233cc	Rear Brakes	Single 220mm petal disc with single- piston caliper	
Bore x Stroke	67.0 x 66.0mm			
Compression Ratio	9.4:1	DETAILS		
Fuel System	DFI® with 32mm Keihin throttle body	Frame Type	High-tensile steel, box-section perimeter	
Ignition	TCBI Electronic Advance	Rake/Trail	26.5°/4.4 in	
Transmission	6-speed, return shift with wet multi-disc manual clutch	Overall Length	80.5 in	
Final Drive	Chain	Overall Width	33.1 in	
		Overall Height	47.2 in	

PERFORMANCE

		Liearance	
Front Suspension /	37mm telescopic fork/9.8 in	Seat Height	36.2 in
Wheel Travel		Curb Weight	253.6 lb / 262.3 lb. CA model*
Rear Suspension /	Uni-Trak® linkage system and single shock with adjustable spring preload/9.9 in 80/100-21	Fuel Capacity	1.7 gal
Wheel Travel		Wheelbase	53.5 in
Front Tire		Color Choices	Lime Green





*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Rear Tire

Ground