2023 KLX[®]230SM







Rear Tire 120/70-17 POWFR **Front Brakes** Single 300mm petal disc with a dual-piston caliper (and ABS) Engine 4-stroke single, SOHC, air-cooled Single 220mm petal disc with single-piston **Rear Brakes** Displacement 233cc caliper (and ABS) **Bore x Stroke** 67.0 x 66.0mm **DETAILS** Compression 9.4:1 Ratio High-tensile steel, box-section perimeter **Frame Type** DFI[®] with 32mm Keihin throttle body **Fuel System** Rake/Trail 27.5°/4.6 in **TCBI** with Electronic Advance Ignition **Overall Length** 80.7 in Transmission 6-speed, return shift with wet multi-disc manual clutch **Overall Width** 32.9 in **Final Drive** Chain **Overall Height** 44.1 in Ground 9.1 in PERFORMANCE Clearance **Seat Height** 33.3 in Front 37mm telescopic fork/8.0 in Suspension / **Curb Weight** 297.7 lb* (ABS), 299.9 lb* (ABS) CA Model / Wheel Travel 295.5 lb* (non-ABS), 297.7 lb* (non-ABS) CA Model Rear Uni-Trak[®] linkage system and single shock with adjustable spring preload/8.6 in Suspension / **Fuel Capacity** 2.0 gal Wheel Travel

Front Tire

Scan with camera

to view videos,

key features

and more.

110/70-17

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When

54.1 in

Lime Green, Oriental Blue

Wheelbase

Color Choices

equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.