

2023

KLX[®]230SM



MSRP NON-ABS
\$3,999

MSRP ABS
\$4,299

-  LIME GREEN
-  ORIENTAL BLUE



POWER

Engine	4-stroke single, SOHC, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.4:1
Fuel System	DFI [®] with 32mm Keihin throttle body
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift with wet multi-disc manual clutch
Final Drive	Chain

PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/8.0 in
Rear Suspension / Wheel Travel	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.6 in
Front Tire	110/70-17

Rear Tire	120/70-17
Front Brakes	Single 300mm petal disc with a dual-piston caliper (and ABS)
Rear Brakes	Single 220mm petal disc with single-piston caliper (and ABS)

DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	27.5° /4.6 in
Overall Length	80.7 in
Overall Width	32.9 in
Overall Height	44.1 in
Ground Clearance	9.1 in
Seat Height	33.3 in
Curb Weight	297.7 lb* (ABS), 299.9 lb* (ABS) CA Model / 295.5 lb* (non-ABS), 297.7 lb* (non-ABS) CA Model
Fuel Capacity	2.0 gal
Wheelbase	54.1 in
Color Choices	Lime Green, Oriental Blue

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.